

Local Phone: 203-575-9220 Toll Free: 1-800-537-7663	MATERIAL SAFETY DATA SHEET 2001 INC. P.O. BOX 2557 WATERBURY, CT 06723-2557 325 THOMASTON AVE. WATERBURY, CT 06702	Business Hours: 8 am – 5 pm Emergency Telephone 1-800-255-3924
--	---	---

MSDS Date: 7/1/04

Supercedes All Previous Publications

Page 1 of 2

=====SECTION I PRODUCT INFORMATION=====

PRODUCT NAME AND SYNONYMS: **CA COMPLIANT PVC ADHESIVE**
 PRODUCT USE: Contact Adhesive

Health	2
Flammability	3
Reactivity	0
Personal Protection	H

=====SECTION II HAZARDOUS INGREDIENTS/SARA III INFORMATION=====

HAZARDOUS COMPONENTS	CAS NUMBER	Occupational Exposure Limits				Vapor Pressure Weight		
		OSHA PEL	ACGIH	TLV	OTHER	mm Eg	@ TEMP	PERCENT
Acetone	67-64-1	750 ppm	750	ppm	1000 STEL	182.0	68F	80

No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 373 are present
 THIS PRODUCT MAY CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

=====SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS=====

<u>Boiling Point</u> 55 degrees C	<u>Vapor Density</u> Heavier Than Air	<u>Coating V.O.C.</u> N/A	<u>Material V.O.C.</u> N/A	<u>Solubility in Water</u> Miscible
<u>Appearance And Odor</u> Medium viscosity liquid w/acetone odor	<u>Specific Gravity (H2O=1)</u> 0.8	<u>Evaporation Rate</u> Slower than Ether		

=====SECTION IV FIRE AND EXPLOSION HAZARD DATA=====

FLASHPOINT: -4 degrees F METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME Lower: 2.2% Upper: 13.0%

EXTINGUISHING MEDIA: Foam, Alcohol Foam, CO2, Dry Chemical

SPECIAL FIREFIGHTING PROCEDURES: Self-contained breathing apparatus is required for fires in enclosed areas.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: Solvent can readily form explosive or flammable mixture in air. Vapors can flow along surfaces to distant ignition sources and flash back.

=====SECTION V REACTIVITY DATA=====

Stability: Stable

Conditions To Avoid: Keep away from all sources of ignition and heat.

Incompatibility (Materials to Avoid): Strong oxidization agents can cause spontaneous combustion.

Hazardous Decomposition or Byproducts: Burning may produce CO2, CO and H2O.

Hazardous Polymerization: Will not occur.

=====SECTION VI HEALTH HAZARD DATA=====

Inhalation Health Risks and Symptoms of Exposure: May cause irritation to upper respiratory tract. Excessive exposure may cause anesthetic or narcotic effects (headache, dizziness, drowsiness).

Skin and Eye Contact Health Risks and Symptoms of Exposure: May cause moderate eye irritation and moderate corneal injury. Vapors may irritate eyes. Prolonged skin exposure may cause drying or flaking of skin.

Skin Absorption Health Risks and Symptoms of Exposure: A single prolonged exposure is not likely to result in the material being absorbed through skin in harmful amounts. The LD50 for skin absorption in rabbits is 20,000 mg/kg.

Ingestion Health Risks and Symptoms of Exposure: Single dose oral toxicity is low. The oral LD50 for rats is >6000 mg/kg. No hazard anticipated for anticipated for ingestion incidental to industrial exposure.

Health Hazards (Acute and Chronic): Excessive exposure to vapors can cause irritation of mucous membranes, dryness of the mouth and throat, headaches, nausea, dizziness, and/or narcosis. Repeated liquid contact will de-fat the skin and may cause dermatitis. Eye contact may cause irritation and burning sensation.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

Medical Conditions Generally Aggravated by Exposure: None identified. Contains no known or suspected carcinogens.

Emergency and First Aid Procedures:

Inhalation: Remove to fresh air; restore breathing, if required; keep warm; get medical attention.

Eye Contact: Wash with large amounts of water for at least 15 minutes; seek medical attention.

Ingestion: Seek immediate medical attention; keep head below hips to prevent aspiration into lungs, should vomiting occur.

Skin Contact: Wash with soap and water; if irritation persists, seek medical attention.

=====SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE=====

Steps to be Taken in Case Material is Released or Spilled: Handle as a flammable liquid. Remove all ignition sources. Soak up wet material on a non-combustible absorbent and place in a closed metal container.

Waster Disposal Method: Dispose in accordance with all local, state and federal regulations.

Precautions to be Taken in Handling and Storing: Store in cool, well-ventilated areas, away from any ignition sources and strong oxidizing agents. Keep containers tightly closed when not in use. Do not transfer to plastic containers.

Other Precautions: Ground and bond metal containers when dispensing. No smoking in areas of use or storage. Use only non-sparking tools near solvent vapors. Solvent vapor much heavier than air and can collect in dangerous concentrations in floor drains or low areas.

=====SECTION VIII CONTROL MEASURES=====

Respiratory Protection: In restricted or non-ventilated areas where vapor exposure may be encountered, use respirator with organic solvent vapor absorbing filter or independent air supply.

Ventilation: Mechanical ventilation and/or local exhaust, sufficient in pattern and volume, to meet TLV requirements and prevent explosive concentrations of solvent vapors.

Protective Gloves: Use polyethylene or natural rubber gloves.

Eye Protection: Safety glasses with splash guards or side shields recommended.

Other Protective Clothing or Equipment: Eye wash fountain or bottles. Solvent insoluble barrier hand cream.

Work/Hygienic Practices: Do not use contact lenses. Wash contaminated clothing before reuse.

=====SECTION VII PREPERATION MEASURES=====

DISCLAIMER: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.