

=====SECTION VI HEALTH HAZARD DATA=====

Permissible Exposure Limit: None established. 500 PPM TWA and 800 ppm STEL recommended for CH₃CCl₂F.

Effects of overexposure: May cause skin or eye irritation upon contact. Avoid breathing vapors. The dense vapors can displace and reduce breathing air in confined or unventilated spaces causing asphyxiation. Overexposure may cause tremors, confusion, irritation, and may result in cardiac sensitization. CH₃CCl₂F vapors can also cause drowsiness, unconsciousness and respiratory depression.

FIRST AID PROCEDURES:

Eye Contact: Flush with water for at least 15 minutes. See a physician if irritation develops.

Skin Contact: Wash with soap and water at first opportunity.

Inhalation: Move to fresh air if symptoms develop. If breathing is difficult, give oxygen and call physician.

Ingestion: Induce vomiting; get medical attention.

=====SECTION VII SPECIAL PROTECTION INFORMATION=====

Ventilation: Local exhaust ventilation is recommended when working with this product. Uses requiring heating and/or spraying may require more ventilation or personal protective equipment.

Respiratory Protection: The specific respirator selected must be based on contamination levels of this materials found in the workplace and must not exceed the working limits of the respirator and be jointly approved by NIOSH and MSHA. Air purifying respirators equipped with full-faced organic vapor cartridge can be used only if isocyanate vapors are not present from the "A" component. In areas of high concentrations, fresh air-line respirators or self-contained breathing apparatus should be used.

Eye Protection: Goggles or chemical safety glasses.

Gloves: Chemically resistant rubber or plastic.

Other: Avoid eye and skin contact. Eye wash system and showers should be available.

=====SECTION VIII SPILL OR LEAK PROCEDURES=====

SPILL OR LEAK PROCEDURES: Remove or extinguish ignition or combustion sources. Contain spill. Absorb with sawdust, etc. and shovel into container. Waste material should be disposed of under conditions which meet federal, state, and local environmental regulations. Wash area with detergent and water.

=====SECTION IX SPECIAL PRECAUTIONS=====

Store between 65° and 85°F out of sunlight. Keep tightly sealed. Relieve pressure slowly when opening container. R Component drums can be sent to drum reconditioners or disposed of as ordinary industrial waste in compliance with pertinent regulations under conditions which meet federal, state, and local environmental regulations.

CAUTION: Under no circumstances should empty drums be burned or cut open with an electric or gas torch.

=====SECTION X SHIPPING INFORMATION=====

Dichlorofluorethane is not regulated when shipped domestically by land or water. If shipped by air (IATA): other regulated substances: Class 9 ID No. 8027 (miscellaneous label).

=====SECTION XI PREPARATION INFORMATION=====

Disclaimer: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

Prepared By: 2001 Inc.