

Local Phone: 203-575-9220

MATERIAL SAFETY DATA SHEET

Business Hours: 8 am -5 pm

Toll Free: 1-800-537-7663

2001 INC.

P.O. BOX 2557 WATERBURY, CT 06723-2557
325 THOMASTON AVE.
WATERBURY, CT 06702

Emergency Telephone

1-800-255-3924

MSDS Date: 03/16/04

Supersedes All Previous Publications

Page 1 of 2

SECTION I PRODUCT INFORMATION

PRODUCT NAME AND SYNONYMS: TPO LAP SEALANT

Table with 2 columns: Hazard Category, Rating. Health: 2, Flammability: 2, Reactivity: 0, Specific Hazard: -

CHEMICAL FAMILY: Elastomeric Sealant
PRODUCT USE: White Lap Sealant
FORMULA: Mixture

SECTION II (A) HAZARDOUS INGREDIENTS

Table with 9 columns: HAZARDOUS INGREDIENT, CAS NUMBER, PEL (ppm), % TWA, STEL, CEILING, SKIN DESIG NATION, LD50OF INGREDIENT (SPECIFY SPECIES & ROUTE) (mg/kg), LC50OF INGREDIENT (SPECIFY SPECIES) (ppm/4H). Rows include Mineral Spirits and Titanium Dioxide.

SECTION II (B) ADDITIONAL INGREDIENTS (>3%)

Table with 2 columns: Ingredients, CAS #. Rows include Ethylene Propylene Terpolymer, Polyalicyclic Hydrocarbon Resin, Calcium Carbonate, and Treated Clay.

SECTION III PHYSICAL DATA

Table with 5 columns: Physical State, Odor and Appearance, VOC (grams/Liter), Odor Threshold (ppm), Vapor Pressure (mm Hg). Rows include Liquid, Vapor Density, Specific Gravity, etc.

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flammability: Yes X No -If Yes, Under Which Conditions? Ignition can occur when this product is exposed to heat, sparks, or Division 2 flame.

Flashpoint (°C) And Method Autoignition Temperature (°C) Lower Flammable Limit (% By Vol) Upper Flammable Limit (% by Vol)
38°C (101°F) TCC 249°C (480°F) 0.70 6.00

Hazardous Combustion Products: Toxic gases or vapors, such as carbon monoxide, carbon dioxide, aldehydes, or oxides of nitrogen may be released in a fire.

EXPLOSION DATA:

Sensitivity To Impact: There is no evidence to show that this product is sensitive to physical shock.
Sensitivity To Static Discharge: As with most hydrocarbon solvents, vapors may ignite when exposed to static discharge.
Extinguishing Media: In case of fire, use dry chemical, carbon dioxide, or foam. Water may not be effective as an extinguishing agent.

Special Fire Fighting Procedures: This product contains solvents that are dangerous fire and explosion hazards when exposed to heat or flame. Fire fighters should wear self-contained breathing apparatus and full protective clothing with a full face piece operated in the positive pressure demand mode.

Unusual Fire And Explosion Hazards: Flammable. Store and use away from all sources of heat, flame, or sparks. Do not smoke while applying. Vapors are heavier than air and may travel along ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electrical motors, static discharge, or other ignition sources at locations distant from material handling point and flash back.

SECTION V REACTIVITY DATA

Chemical Stability: Stable Hazardous Polymerization: Will not occur.
Conditions to Avoid: Heat, sparks, and flames; ignition sources.
Incompatibility (Materials to Avoid): Strong oxidizing agents, acids and bases.
Hazardous Decomposition Products: Toxic gases or vapors, such as carbon monoxide, carbon dioxide, aldehydes, or oxides of nitrogen may be released in a fire.

=====SECTION VI TOXICOLOGICAL PROPERTIES=====

Route of Entry: Skin Contact X Skin Absorption X Eye Contact X Inhalation X Ingestion X

Effects of Acute Exposure To Product: Skin, eye, nose and throat irritation on short term exposure to liquid or vapor. Overexposure may result in headache, dizziness, fatigue, nausea and loss of consciousness. Solvents may be absorbed through the skin in toxic amounts. Ingestion causes irritation of gastrointestinal tract.

Effects of Chronic Exposure: Chronic exposure may cause reversible kidney and liver injury. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Exposure Limits	Irritancy of Product	Sensitizations To Product	Carcinogenicity
OSHA PEL-TWA Mineral Spirits: 100 ppm	Eye, nose, and throat irritation at or above vapor concentration of 100 ppm.	None known	None known

Teratogenicity	Reproductive Toxicity	Mutagenicity	Synergistic Products	Tumorigenicity
No evidence	No evidence	No evidence	None known	No evidence

=====SECTION VII PREVENATIVE MEASURES=====

PERSONAL PROTECTIVE EQUIPMENT:

- Gloves: Hycron® or equivalent solvent permeation resistant gloves recommended.
- Respirator: Approved NIOSH respirator must be used if vapor concentration is 300 ppm or above.
- Eye: Protective glasses or goggles recommended.
- Footwear: Industrial boots to protect feet from sealant contact.
- Clothing: Long sleeves, long trousers to protect skin from sealant contact.
- Other: Protective skin creams or emollients useful.

Engineering Controls (EG., Ventilation, Enclosed Process): Do not use in enclosed areas without proper explosion-proof ventilation. General and local exhaust ventilation must be sufficient to control vapor concentrations and keep the vapor concentration below 300 ppm.

Leak or Spill Procedure: Remove all sources of ignition. Avoid breathing vapors. Use self-contained breathing apparatus in enclosed area. Ventilate area. Contain and remove with inert absorbent materials and non-sparking tools.

Waste Disposal: Dispose of in accordance with all local, state, and federal regulations.

Handling Procedures and Equipment: Use away from all sources of heat, flame, or sparks. Do not smoke while using. Handling equipment must be grounded to prevent sparking. Handle with non-sparking tools. Wash with soap and water before eating or drinking. Launder contaminated clothing. KEEP OUT OF REACH OF CHILDREN.

Storage Requirements: Keep containers cool and dry; store away from all sources of heat, flame, and sparks. Keep containers tightly closed and store with adequate ventilation. Do not pressurize, cut, weld, or grind the containers or empty containers which may contain residual product and solvent vapors that may ignite explosively.

Special Shipping Information: A red Flammable Liquid Label is required for 5 gallon pails. DOT Classification: Adhesives, 3, UN1133, PGI. Cartridges may be shipped as Limited Quantity, not requiring the label.

=====SECTION VIII FIRST AID MEASURES=====

- Specific Measures: Whenever possible, remove the worker from the source of contamination.
- Eye Contact: Immediately flush eyes with running water for at least 15 minutes. Get medical attention.
- Skin Contact: Immediately flush skin with running water and remove contaminated clothing. Wash exposed area with soap and water. Get medical attention.
- Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention immediately.
- Ingestion: DO NOT induce vomiting. Get medical attention immediately.

Respiratory symptoms associated with pre-existing lung disorders and pre-existing heart disorders may be aggravated by exposure to this material.

=====SECTION IX ADDITIONAL REGULATORY INFORMATION=====

California Proposition 65
This product contains the following chemical (s) known to the state of California to cause cancer: NONE

=====SECTION X PREPARATION INFORMATION=====

Disclaimer: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.