

=====SECTION V FIRE-FIGHTING MEASURES=====

Flash Point: 4.40°C (40°F)
 Flash Point Method: CC
 Autoignition Temperature: 536°C (997°F)
 UEL: 1.3% v/v
 UEL: 7.0% v/v

Flammability Classification: Ignition can occur when this product is exposed to heat, Division 2 sparks, or flame.
Extinguishing Media: In case of fire, use dry chemical, carbon dioxide, or foam. Water may not be effective as an extinguishing agent. Water fog or spray may be used to provide a smothering effect on fire and to cool fire-exposed containers and surrounding combustibles. Do not use a solid stream of water because it can scatter and spread the fire.
Unusual Fire or Explosion Hazards: Extremely flammable. Store and use away from all sources of heat, flame, or sparks. Do not smoke while applying. Vapors are heavier than air and may travel along ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electrical motors, static discharge, or other ignition sources at locations distant from material handling point and flash back. All containers should be grounded when material is transferred.
Hazardous Combustion Products: Toxic gases or vapors, such as carbon monoxide or carbon dioxide, may be released in a fire.
Fire-Fighting Instructions: This product contains solvents that are dangerous fire and explosion hazards when exposed to heat or flame.
Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) and full protective clothing along with a full face piece operated in pressure-demand or positive-pressure mode.

=====SECTION VI TYPICAL PROPERTIES & CHARACTERISTICS=====

Base	Synthetic Rubber
Color	Bronze to Olive Drab
Solids	18%
Flash Point	40°F (4.4°C)
Average Net Weight	7.5 lbs/gal (.9 Kg/liter)
Packaging	6-1 gallon pails/carton or 1-2.5 gallon pail
Shelf Life	6 months

CAUTIONS AND WARNINGS:

1. This product is FLAMMABLE. Precautions must be taken to keep the primer away from heat, flame and sparks during storage and use.
2. Keep container closed when not in use. Use with adequate ventilation. Avoid breathing vapors. Avoid contact with eyes and skin.
3. Chemically resistant gloves must be worn with primer to protect hands from staining and irritation. Hycron® gloves are designed for this purpose.
4. Thoroughly stir this product until all settled pigment is blended into the solution. Solids suspended in primer tend to settle. Stir or agitate the solution frequently during use (every 15-20 minutes).
5. Use full strength. Do not thin. Thinning will affect performance.
6. Primer may cause staining of white membrane and other non-black surfaces.
7. Job site storage temperatures in excess of 90°F may affect product shelf life. Should the primer be stored at temperatures lower than 60°F, restore to room temperature prior to use.
8. Keep can tightly closed when not in use to protect from moisture contamination. Once exposed to moisture in the air, primer begins to cure and may gel within a few days. A gasket of membrane or sealant can be used to create a positive seal.
9. Due to solvent flash-off, condensation may form on freshly applied primer when the ambient temperature is near the dew point. If condensation develops, the application of primer must be discontinued (proper adhesion will not be obtained). Allow the surface to dry and apply a thin fresh coat of primer to the previously coated surface when conditions allow.
10. REVIEW THE PRIMER SAFETY DATA SHEET FOR COMPLETE SAFETY INFORMATION PRIOR TO USE.
11. KEEP OUT OF THE REACH OF CHILDREN.

=====SECTION VII PREPARATION INFORMATION=====

DISCLAIMER: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations. Prepared By: 2001 Inc.