

Local Phone: 203-575-9220

MATERIAL SAFETY DATA SHEET

Business Hours: 8 am - 5 pm

Toll Free: 1-800-537-7663

2001 INC.
P.O. BOX 2557 WATERBURY, CT 06723-2557
325 THOMASTON AVE.
WATERBURY, CT 06702

Emergency Telephone

1-800-255-3924

MSDS Date: July 17, 2006

Supersedes All Previous Publications

Page 1 of 2

SECTION I PRODUCT INFORMATION

PRODUCT NAME AND SYNONYMS: TALC EATER III

SECTION II HAZARDOUS INGREDIENTS INFORMATION

CHEMICAL NAME	CAS NUMBER	% TWA	STEL	ACGIH TLV	OSHA PEL
Light Aliphatic Solvent Naphtha	64742-89-8	40-60		300 ppm	500 ppm
Aromatic Hydrocarbon Solvent	108-88-3	20-40		100 ppm	200 ppm

SECTION III PHYSICAL AND CHEMICAL DATA

Appearance & Odor: Clear liquid with characteristic aliphatic solvent odor.
Physical State: Liquid **Boiling Point:** 185°F
Specific Gravity (water=1): 0.75-0.81 **Evaporation Rate (ethyl ether=1):** 3.5
Percent Volatiles: 85% **Solubility in Water:** Insoluble
Vapor Pressure: 38 mm Hg @68°F, 20°C **Vapor Density (air=1):** 3.6
Percent Solids (by weight): 15% **Melting Point:** N.A.
VOC: 645 grams/liter

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point: 18° Method Used: Estimate based on the flash point of the most volatile component.

Flammable Limits: LEL: 1.2% UEL: N.A.

Proper Extinguishing Media: Foam, dry chemical or carbon dioxide. Water may be ineffective, but water should be used to keep fire exposed containers cool.

Recommended Firefighting Procedures: Treat as a class "B" fire. Limit fire fighting to those trained to do so. If a leak or spill has ignited, use water spray to disperse the vapors and to protect the men attempting to stop the leak. Minimize breathing gases, vapor, fumes, or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

Unusual Fire & Explosion Hazards: Vapors are heavier than air and may travel along the ground and be ignited by ignition sources distant from the handling point. Residue in "empty" containers may be explosive if exposed to an ignition source. To prevent fire or explosion from static accumulation and discharge, effectively ground the product transfer system.

SECTION V HEALTH HAZARD DATA

Medical Conditions Aggravated by Exposure: Pre-existing eye, skin, and pulmonary disorders may be aggravated by exposure to this product.

Primary Route of Entry:	Skin absorption	yes
	Inhalation	yes
	Ingestion	yes
	Eye contact	yes

Signs and Symptoms of Exposure:

Eye Contact: Can cause severe irritation, redness, tearing, blurred vision.
Skin Contact: Can cause redness, irritation, dermatitis.
Inhalation: Prolonged inhalation of vapors may cause irritation of the respiratory tract. Intentional misuse by deliberately concentrating and inhaling vapor may be harmful or fatal.
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

Emergency and First Aid Procedures:

In Eyes: Flush with large amounts of water, frequently flushing under the lids. Seek medical attention.
On Skin: Wash with soap and water. Get medical attention if irritation persists.
Inhaled: Remove affected person to fresh air, give oxygen or artificial respiration as necessary to assist breathing. Get medical attention
Ingested: Do not induce vomiting. Get medical attention.

Acute Effects of Overexposure: Irritation, redness.

Chronic Effects: (Include all potential carcinogens present @ .1% or greater). Prolonged or repeated contact with the skin can cause moderate irritation, dermatitis.

Carcinogenicity: NTP? No

IARC Monographs? No

OSHA Regulated? No

=====SECTION VI REACTIVITY DATA=====

Stability: Stable

Conditions to Avoid: None known.

Hazardous Decomposition Products: In the event of partial combustion, fumes, smoke, carbon monoxide, aldehydes, and other decomposition products may be released.

Hazardous Polymerization: Will Not Occur

Incompatibility: Avoid contact with strong oxidizing agents.

=====SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE=====

Ventilation:

General exhaust as needed to keep TLV below recommended levels if engineering or administrative controls are not adequate.

Personal Protective Equipment:

Respirator: For large spills or entry into enclosed small spaces with inadequate ventilation, a pressure demand, self-contained breathing apparatus is recommended. If engineering or administrative controls are not adequate to maintain solvent TLV below recommended levels, an appropriate respirator should be used in conjunction with a respirator use and fit training program.

Gloves: Buna-N, if needed.

Eye Protection: Safety glasses with side shields.

Other Protective Clothing/Articles: To prevent repeated or prolonged skin contact, wear impervious clothing and boots if contact is likely.

Work/Hygienic Practices: Minimize breathing vapor. Avoid prolonged or repeated contact with the skin. Remove contaminated clothing and launder before reuse. Cleanse skin thoroughly after contact, before work breaks and meals, and at the end of the work day. Product is readily removed from the skin with waterless hand cleaners followed by washing thoroughly with soap and water. Eye wash stations should be available where product may come in contact with the eyes.

Steps To Be Taken in Case Material is Released or Spilled: Eliminate all ignition sources. Control the source of the spill if it is safe to do so. Ventilate enclosed areas to prevent vapor accumulation. Restrict access by unauthorized personnel. Absorb spilled product with vermiculite or other absorbent material. Shovel or scoop into a sealable container for disposal.

Waste Disposal Method: If this product becomes a waste, it is considered a hazardous waste due to its ignitability. Dispose of in accordance with local, state, and federal environmental and waste regulations.

Storage and Handling Procedures: Do not store or handle near an ignition source. Keep containers closed. Effectively ground the product transfer system to prevent fire or explosion from static discharge. Empty containers may contain residual product. Do not reuse containers unless properly reconditioned.

=====SECTION VIII REGULATORY INFORMATION=====

All components are included in the EPA toxic Substance Control Act (TSCA) Chemical Substance Inventory.

If this product becomes a waste, it meets the criteria of a hazardous waste as defined under RCRA 40CF261: ignitability

Hazardous Materials Identification System (HMIS):

Health Hazard Rating: 1 CAUTION Irritation or minor reversible injury possible.
Flammability Hazard Rating: 3 WARNING Material capable of ignition under almost all normal temperature conditions.
Reactivity Hazard Rating: 0 Normally stable and will not react with water.
Personal Protective Equipment: H Safety glasses, gloves, apron, vapor respirator.

EPA SARA Title III hazard class (40CFR370): Acute Health Hazard
Chronic Health Hazard
Fire Hazard

EPA SARA Title III Section 313 (40CFR372): Aromatic hydrocarbon solvent C.A.S.# 108-88-3 20-40%

EPA SARA Title III (40CFR355): There are no components present in this product at a level which would require reporting.

DOT Shipping Name: Adhesives, containing flammable liquid
DOT Hazard Class: 3
DOT ID Number: UN1133
DOT Packing Group: II

This product contains a chemical that is listed on the following states hazardous material list.

Pennsylvania Hazardous Substance List: YES New Jersey Workplace Hazardous Substance List: YES
Massachusetts Substance List: YES Canada (WHMIS) Ingredient Disclosure List: YES

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This product contains listed substances, which the state of California has found to cause cancer, birth defects, or other reproductive harm, which would require a warning under the statute. Toluene CAS 108-88-3

=====SECTION IX PREPARATION INFORMATION=====

DISCLAIMER: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations. Prepared By: 2001 Inc.